

UNICOAT ADMIXTURE 2000

UNICOAT STUCCO SYSTEMS



PRODUCT DATA SHEET

PRODUCT DESCRIPTION

UNICOAT ADMIXTURE 2000 is a 100% acrylic emulsion admixture agent used to enhance the performance of cement based products. **UNICOAT ADMIXTURE 2000** also enhances the flexural and compression strengths, as well as freeze thaw and faster curing traits. **UNICOAT ADMIXTURE 2000** comes in quarts, gallons, and 5 gallon pails.

APPROVED SUBSTRATES

UNICOAT ADMIXTURE 2000 may be mixed into one-coat and 3-coat cement mixes, concrete and masonry mortar mixes, and portland cement grouts and cement based stucco finishes.

MIXING AND APPLICATION

Mix **UNICOAT ADMIXTURE 2000** into the clean water used for mixing cement mix before adding cement product.
Use approximately 4% to 20% of **UNICOAT ADMIXTURE 2000** of water content, depending on mix and application.
Recommended ratio is to replace 1 gallon of water per 80 lbs of cement based product.
Use Rubber gloves when using this product.

STORAGE, SHELF LIFE AND COVERAGE

UNICOAT ADMIXTURE 2000 should be stored in a cool dry place, away from direct sunlight and protected from extreme heat and freezing conditions. Always keep container closed when not in use.
UNICOAT ADMIXTURE 2000 has a shelf life of 12 months when properly stored. If product starts to turn moldy, do not use or throw down the drains. The best way to dispose of gallon after expiration is to pour out on top of a Sand mound outside in a well ventilated area. Let product dry in the sand and then dispose of dried glued sand.
Do not mix product with any other liquids that may cause a chemical reaction. Use for intended purposes only.

LIMITATIONS AND MANUFACTURER'S WARRANTY

UNICOAT ADMIXTURE 2000 may alter the color of the material to which it is introduced.
Always make a sample of the finish coat if the color is important. Cement based products modified with this product should be allowed to cure in ambient temperatures above 40 deg f and under 110 deg f. Always protect cement mixes from rain and moisture for 48 hrs. after application.
UNICOAT ADMIXTURE 2000 is warranty free from manufacturing defects only.
Since we have no control of the end use of this product, no warranties are made on finished product.
The sole warranty is replacement of materials used to correct defective material: no other warranties are either expressed or implied.



PROJECT INFORMATION		ARCHITECT INFORMATION	
NAME:		NAME	
ADDRESS:		ADDRESS	
		CONTACT	
CONTRACTOR INFORMATION		PHONE	
NAME:		DISTRIBUTOR	
ADDRESS:		NAME	
PHONE:		ADDRESS	