

UNICOAT SUPER BOND 1000

UNICOAT STUCCO SYSTEMS



PRODUCT DATA SHEET

PRODUCT DESCRIPTION

UNICOAT SUPER BOND 1000 is a 100% acrylic emulsion bonding agent used to bond new stucco and concrete to old stucco and concrete.

UNICOAT SUPER BOND 1000 can also bond new stucco to painted surfaces (flat finish only), and can be left dry for up to 5 days to be able to bond.

UNICOAT SUPER BOND 1000 comes in quarts, gallons, and 5 gallon pails.

APPROVED SUBSTRATES

UNICOAT SUPER BOND 1000 may be applied over old stucco, old concrete and masonry surfaces, painted surfaces (flat finish only), and any primed metal or wood surface.

MIXING AND APPLICATION

UNICOAT SUPER BOND 1000 can be applied with a paint roller, brush, or sprayer. Product comes tinted yellow to be able to see areas covered when it begins to dry. Apply a thin even coat over substrate. Do not glob product in certain areas. Try to keep a uniform pattern when applying with a roller, paint brush or spray device.

Product to be bonded can be applied immediately after bonding agent has been applied.

When bonding agent has dried, lightly mist surface and then apply product over bonding agent.

If more than 5 days has elapsed after application of bonding agent, reapply a new coat of bonding agent.

Use Rubber gloves when using this product.

STORAGE, SHELF LIFE AND COVERAGE

UNICOAT SUPER BOND 1000 should be stored in a cool dry place, away from direct sunlight and protected from extreme heat and freezing conditions.

Always keep container closed when not in use.

UNICOAT SUPER BOND 1000 has a shelf life of 12 months. If product starts to turn moldy, do not use or throw down the drains. The best way to dispose of gallon after expiration is to pour out on top of a Sand mound outside in a well ventilated area. Let product dry in the sand and then dispose of dried glued sand.

Do not mix product with any other liquids that may cause a chemical reaction. Use for intended purposed only.

UNICOAT SUPER BOND 1000 covers approximately 200-300 sq ft per gallon.

LIMITATIONS AND MANUFACTURER'S WARRANTY

UNICOAT SUPER BOND 1000 must be applied to a clean surface free from all foreign matter, efflorescence, oil, dirt, and any other bond inhibiting material.

Do not use this product as an admixture.

Painted surfaces should be at least several months old.

All loose paint or debris should be removed prior to bonding application.

UNICOAT SUPER BOND 1000 is warranted free from manufacturing defects only.

Since we have no control of the end use of this product, no warranties are made on finished product.

The sole warranty is replacement of materials used to correct defective material: no other warranties are either expressed or implied.



PROJECT INFORMATION		ARCHITECT INFORMATION	
NAME:		NAME	
ADDRESS:		ADDRESS	
CONTRACTOR INFORMATION		CONTACT	
NAME:		PHONE	
ADDRESS:		DISTRIBUTOR	
PHONE:		NAME	
		ADDRESS	