PERMACOAT ELASTOMERIC STUCCO FINISH

UNICOAT
STUCCO SYSTEMS

PRODUCT SUBMITTAL SHEET

PRODUCT DESCRIPTION

PERMACOAT ELASTOMERIC STUCCO FINISH is a 100% Elastomeric acrylic stucco finish for exterior use only on above grade walls and previously coated surfaces. This flexible vapor permeable finish can bridge most hairline cracks on stucco base coats.
PERMACOAT ELASTOMERIC STUCCO FINISH can be used over EIFS base coats, stucco, concrete surfaces and all Unicoat base coats.
PERMACOAT ELASTOMER STUCCO FINISH comes in various textures: Medium and Coarse sand, Medium and Coarse rilled, and Fine.

APPROVED SUBSTRATES

PERMACOAT ELASTOMERIC STUCCO FINISH can be applied over new and old stucco, concrete and masonry surfaces, painted surfaces (flat finish only), and all one-coat and 3-coat base coat applications.

When applying over new stucco and concrete surfaces, it is always recommended that walls be cured out completely and a coat of Unicoat Surface Primer 870 be applied.

Make sure all surfaces are clean before applying finish.

MIXING AND APPLICATION

PERMACOAT ELASTOMERIC STUCCO FINISH should be mixed in its own container using a low rpm drill mixer to ensure color uniformity and minimize air entrapment.

*Do not thin this product with more than 1 pint of clean water.
*Apply in one coat at approximately 1/8" thickness over substrate.
*This product can be applied by hand trowel application only.
*Spray application is possible in sand finish texture only, please consult with manufacturer for proper procedure.
*It is highly recommended that a professional platering applicator apply this product to attain desired texture and uniformity.

DRY TIME, SHELF LIFE AND COVERAGES

PERMACOAT ELASTOMERIC STUCCO FINISH should be stored in a cool dry place, away from direct sunlight and protected from extreme heat and freezing conditions.
*Always keep container closed when not in use, product has a shelf life of 12 months when these directions are follwed.
*This product covers approximately 90-150 sq ft per pail, depending on proosity of surface and texture application.
*Drying time is 4 hours at 70deg F if applied as per spectifications.
*Always protect from appying in freezing or rainy conditions for at least 24 hrs.

LIMITATIONS AND MANUFACTURER'S WARRANTY

PERMACOAT ELASTOMERIC STUCCO FINISH must be applied to a clean surface free from all foreign loose matter, efforescence, oil, dirt, and any other bond inhibiting materials.
*Do not use this product in extreme heat and in freezing conditions.
*Painted surfaces should be at least several months old.
*All loose paint should be removed.

PERMACOAT ELASTOMER STUCCO FINISH can be warranted for up to 10 years when applied by an approved applicator and all CCRR Code compliance standards are fullfilled.

The sole warranty is replacement of materials used ot correct defective materials: no other warranties are either expressed or implied.

This product will bridge hairline cracks in most stucco walls but it is not a crack proof product. There is no warranty against cracks breaking through the finish product.

SOMAR INDUSTRIES LTD.

PROJECT INFORMATION
NAME:
ADDRESS:
CONTRACTOR INFORMATION
NAME:
ADDRESS:
PHONE:

ARCHITECT INFORMATION
NAME
ADDRESS
CONTACT
PHONE
DISTRIBUTOR
NAME
ADDRESS