


# CEMENT WORKS 1/2" CHOPPED FIBERGLASS

# UNICOAT STUCCO SYSTEMS



## PRODUCT SUBMITTAL SHEET

### PRODUCT DESCRIPTION

**CEMENT WORKS 1/2" CHOPPED FIBERGLASS STRANDS** are fiberglass strands for use in all types of cement and stucco mixes for added crack resistance and more overall flexural strength. These fibers are alkali resistant to ensure long term life of the product in the mix. This product comes packaged in 5 lb. boxes and 50 lb. Bags.

### GENERAL INSTRUCTIONS

**CEMENT WORKS 1/2" CHOPPED FIBERGLASS STRANDS** are mixed in with cement and stucco mixtures to achieve more crack resistance and more flexural strength. When mixing in concrete mixes, add approximately 3 to 4 lbs. per 94 lb. cement or per cubic yard of redi-mixed concrete. For stucco mixes add approximately 2 to 3 lbs. per 94 lbs. portland cement. Add fiberglass strands to mix at any time during the mix, making sure that it is mixed evenly in the mixture. Do not add more fibers than what is recommended for weakening of cement will occur.

### LIMITATIONS AND MANUFACTURER'S WARRANTY

**CEMENT WORKS 1/2" CHOPPED FIBERGLASS STRANDS** should always have care when mixing with this product. Somar Industries Ltd. will not warrant finish work having no control for the end use of this product. There are no other warranties either expressed or implied. Somar Industries Ltd. assumes no liability for the end-use of this product and for incidents that may occur when using this product.

### IMPORTANT NOTES AND CAUTIONS

Always wear protective clothing, gloves, eye protection, and dust mask when working with this product. Care should always be taken when using this product, do not breathe fiberglass particles that may occur. These fiberglass strands are to enhance the performance of concrete, but are not a replacement for structural steel reinforcement.



#### PROJECT INFORMATION

NAME:  
ADDRESS:

#### CONTRACTOR INFORMATION

NAME:  
ADDRESS:  
PHONE:

#### ARCHITECT INFORMATION

NAME  
ADDRESS  
CONTACT  
PHONE

#### DISTRIBUTOR

NAME  
ADDRESS