

UNICOAT FOAM and STUCCO PATCH

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Date of Issue: 06/11/2024

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: UNICOAT FOAM and STUCCO PATCH

Product Code: 280

1.2. Intended Use of the Product

Use of the Substance/Mixture: FOR EXTERIOR USE ONLY

1.3. Name, Address, and Telephone of the Responsible Party

Company

Somar Industries Ltd.

6050 Lockett Court

El Paso, TX 79932

(915) 858-8080

1.4. Emergency Telephone Number

Emergency Number : (915) 727-0877

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US Classification

Skin corrosion/irritation Category 1C H314

Serious eye damage/eye irritation Category 1 H318

Skin sensitization, Category 1 H317

Carcinogenicity Category 1A H350

Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation H335

Specific target organ toxicity (repeated exposure) Category 1 H372

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.
H350 - May cause cancer (Inhalation).
H372 - Causes damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation).

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, and eye protection.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a poison center or doctor.
P321 - Specific treatment (see section 4 on this SDS).

UNICOAT FOAM and STUCCO PATCH

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	%	GHS US classification
Proprietary Ingredient 1	Proprietary	(CAS-No.) Proprietary	< 42.55	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Proprietary Ingredient 2*	Proprietary	(CAS-No.) Proprietary	34.58	See classifications of constituent ingredients in table below
Proprietary Ingredient 3	Proprietary	(CAS-No.) Proprietary	21.08 – 21.52	Not classified.
Proprietary Ingredient 4	Proprietary	(CAS-No.) Proprietary	< 1.19	Not classified.
Proprietary Ingredient 5	Proprietary	(CAS-No.) Proprietary	< 0.001	Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

* Proprietary Ingredient 2 has a variable composition, comprised of:

Proprietary Ingredient 2 content(s)	Synonyms	Product Identifier	%	GHS US classification
Proprietary Ingredient 6	Proprietary	(CAS-No.) Proprietary	8 – 28	Skin Irrit. 2, H315 Eye Dam. 1, H318
Proprietary Ingredient 7	Proprietary	(CAS-No.) Proprietary	≤ 28	Not classified
Proprietary Ingredient 8	Proprietary	(CAS-No.) Proprietary	4 – 24	Eye Irrit. 2A, H319
Proprietary Ingredient 3	Proprietary	(CAS-No.) Proprietary	≤ 11	Not classified
Proprietary Ingredient 9	Proprietary	(CAS-No.) Proprietary	3.2 – 9.4	Not classified
Proprietary Ingredient 10	Proprietary	(CAS-No.) Proprietary	0.4 – 6	Eye Irrit. 2A, H319
Proprietary Ingredient 11	Proprietary	(CAS-No.) Proprietary	2 – 6	Eye Irrit. 2A, H319
Proprietary Ingredient 12	Proprietary	(CAS-No.) Proprietary	≤ 6	Not classified
Proprietary Ingredient 13	Proprietary	(CAS-No.) Proprietary	≤ 6	Not classified
Proprietary Ingredient 14	Proprietary	(CAS-No.) Proprietary	0.39 – 4	Not classified
Proprietary Ingredient 15	Proprietary	(CAS-No.) Proprietary	≤ 3	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

UNICOAT FOAM and STUCCO PATCH

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proprietary Ingredient 1	Proprietary	(CAS-No.) Proprietary	< 0.46	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Proprietary Ingredient 16	Proprietary	(CAS-No.) Proprietary	≤ 0.032	Not classified
Proprietary Ingredient 17	Proprietary	(CAS-No.) Proprietary	< 0.006	Skin Sens. 1, H317 Carc. 1B, H350 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: Using proper respiratory protection, immediately move the exposed person to fresh air. Encourage exposed person to cough, spit out, and blow nose to remove dust. Give oxygen or artificial respiration if necessary. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 60 minutes. Use a pH-neutral or slightly acidic soap. Get immediate medical advice/attention. Seek medical attention to remove hardened material from skin. Wash contaminated clothing before reuse.

First-aid Measures After Eye Contact: Immediately rinse with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: Causes severe skin burns and eye damage. May cause respiratory irritation. Skin sensitization. Causes damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation). May cause cancer (Inhalation).

Symptoms/Injuries After Inhalation: Irritation of the respiratory tract and the other mucous membranes. Cough, dyspnea (breathing difficulty), wheezing; decreased pulmonary function, progressive respiratory symptoms (silicosis). The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels. Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis. Progressive massive fibrosis may occur in simple or accelerated silicosis, but is more common in the accelerated form. Progressive massive fibrosis results from severe scarring and leads to the destruction of normal lung structures.

Symptoms/Injuries After Skin Contact: Causes severe irritation which will progress to chemical burns. May cause an allergic skin reaction. Cement may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns. A skin exposure may be hazardous even if there is no pain or discomfort. Cement is capable of causing dermatitis by irritation and allergy. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Irritant dermatitis is caused by the physical properties of cement including alkalinity and abrasion. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in cement. The reaction can range from a mild rash to severe skin ulcers. Persons already sensitized may react to the first contact with cement. Others may develop allergic dermatitis after years of repeated contact with cement.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva. Airborne dust may cause immediate or delayed irritation or inflammation. Eye contact with large amounts of dry powder or with wet cement can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

Symptoms/Injuries After Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic Symptoms: Causes damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation). May cause cancer (Inhalation). This product contains crystalline silica. Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis; a seriously disabling and fatal lung disease, and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects. Inhalation may lead to a progressive massive fibrosis which may be accompanied by right heart enlargement, heart failure, pulmonary failure of the lung and susceptibility to pulmonary tuberculosis. Pulmonary function may be reduced and pre-existing lung diseases such as: emphysema or asthma may be aggravated by inhalation exposure to dusts. Smoking aggravates the effects of exposure.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand. Treatment will be based on severity and prognosis of disease.

UNICOAT FOAM and STUCCO PATCH

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Reacts with water.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Wet cement is alkaline and is incompatible with acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Oxides of magnesium. Calcium oxides. Silica compounds. Aluminum oxides. Metal oxides. Crystalline silica exists in several forms, the most common of which is quartz. If crystalline silica (quartz) is heated to more than 870°C (1598 °F), it can change to a form of crystalline silica known as tridymite, and if crystalline silica (quartz) is heated to more than 1470°C (2678 °F), it can change to a form of crystalline silica known as cristobalite. The OSHA PEL for crystalline silica as tridymite and cristobalite is one-half of the OSHA PEL for crystalline silica (quartz).

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not get in eyes, on skin, or on clothing.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Ventilate area. For wet cement: Remove product by scooping or shoveling into suitable containers for recycling or disposal, utilize appropriate PPE (see Section 8). For dry cement, or if it becomes hardened: Avoid generation of dust. Vacuum cleanup is preferred, if sweeping is required use a dust suppressant, do not dry sweep. Utilize appropriate PPE (see Section 8). Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

UNICOAT FOAM and STUCCO PATCH

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Wet cement is corrosive. Take appropriate precautions to prevent unnecessary contact. Cement may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns. A skin exposure may be hazardous even if there is no pain or discomfort. Cement is capable of causing dermatitis by irritation and allergy. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Irritant dermatitis is caused by the physical properties of cement including alkalinity and abrasion. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in cement. The reaction can range from a mild rash to severe skin ulcers. Persons already sensitized may react to the first contact with cement. Others may develop allergic dermatitis after years of repeated contact with cement. Cutting, crushing or grinding cement clinker, hardened cement, concrete or other crystalline silica-bearing materials will release respirable crystalline silica. Use all appropriate measures of dust control or suppression, and Personal Protective Equipment (PPE) described in Section 8 below.

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe dust. If clothing is contaminated with wet cement, promptly remove clothing to avoid chemical burns. Use appropriate personal protective equipment (PPE). Handle empty containers with care because they may still present a hazard. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Wet cement and cement clinker is alkaline and is incompatible with acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

7.3. Specific End Use(s)

FOR EXTERIOR USE ONLY

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Proprietary Ingredient 2		
USA ACGIH	ACGIH OEL TWA	1 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA IDLH	IDLH	5000 mg/m ³
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA OSHA	OSHA PEL (TWA) [2]	50 mppcf (<1% Crystalline silica) (See 29 CFR 1910.1000 TABLE Z-3)
Proprietary Ingredient 4		
USA ACGIH	ACGIH OEL TWA	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Particulates not otherwise classified (PNO)		
USA ACGIH	ACGIH OEL TWA	3 mg/m ³ Respirable fraction

UNICOAT FOAM and STUCCO PATCH

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		10 mg/m ³ Total Dust
USA OSHA	OSHA PEL (TWA) [1]	5 mg/m ³ Respirable fraction 15 mg/m ³ Total Dust
USA OSHA	OSHA PEL (TWA) [2]	15 mppcf (respirable fraction) 50 mppcf (total dust) See 29 CFR 1910.1000 Table Z-3
Proprietary Ingredient 3		
USA NIOSH	NIOSH REL (TWA)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Proprietary Ingredient 1		
USA ACGIH	ACGIH OEL TWA	0.025 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	Suspected Human Carcinogen
USA NIOSH	NIOSH REL (TWA)	0.05 mg/m ³ (respirable dust)
USA IDLH	IDLH	50 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) [1]	50 µg/m ³ (Respirable crystalline silica)
USA OSHA	OSHA PEL (TWA) [2]	(250)/(%SiO ₂ +5) mppcf TWA (respirable fraction) (10)/(%SiO ₂ +2) mg/m ³ TWA (respirable fraction) (For any operations or sectors for which the respirable crystalline silica standard, 1910.1053, is stayed or otherwise not in effect, See 20 CFR 1910.1000 TABLE Z-3)
Proprietary Ingredient 9		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³ (inhalable particulate matter (Calcium sulfate))
USA NIOSH	NIOSH REL (TWA)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Proprietary Ingredient 12		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³ (inhalable particulate matter (Calcium sulfate))
Proprietary Ingredient 14		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA IDLH	IDLH	750 mg/m ³ (fume)
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (fume, total particulate)
Proprietary Ingredient 15		
USA ACGIH	ACGIH OEL TWA	2 mg/m ³
USA NIOSH	NIOSH REL (TWA)	2 mg/m ³
USA IDLH	IDLH	25 mg/m ³
USA OSHA	OSHA PEL (TWA) [1]	5 mg/m ³
Proprietary Ingredient 17		
USA OSHA	OSHA PEL (TWA) [1]	5 µg/m ³
USA OSHA	OSHA Action Level/Excursion Limit	2.5 µg/m ³ (Action level, see 29 CFR 1910.1026)

8.2. Exposure Controls

Appropriate Engineering Controls

: Ensure adequate ventilation, especially in confined areas. Maintain sufficient mechanical or natural ventilation to assure silica concentrations remain below PEL/TLV. Use local exhaust if necessary. Power equipment should be equipped with properly designed dust collection devices. If product needs to be altered, use wet processing techniques if possible to minimize generation of dust. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

UNICOAT FOAM and STUCCO PATCH

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear protective gloves.

Eye and Face Protection

: Chemical safety goggles.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Gray powder
Odor	: No data available
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

9.2. Other Information

No additional information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Wet cement is alkaline and is incompatible with acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

10.2. Chemical Stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, and incompatible materials. Avoid creating or spreading dust.

10.5. Incompatible Materials

Wet cement and cement clinker is alkaline and is incompatible with acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

10.6. Hazardous Decomposition Products

UNICOAT FOAM and STUCCO PATCH

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Thermal decomposition may produce: Crystalline silica exists in several forms, the most common of which is quartz. If crystalline silica (quartz) is heated to more than 870°C (1598 °F), it can change to a form of crystalline silica known as trydimite, and if crystalline silica (quartz) is heated to more than 1470°C (2678 °F), it can change to a form of crystalline silica known as cristobalite. The OSHA PEL for crystalline silica as trydimite and cristobalite is one-half of the OSHA PEL for crystalline silica (quartz).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity (Oral): Not classified.

Acute Toxicity (Dermal): Not classified.

Acute Toxicity (Inhalation): Not classified.

Proprietary Ingredient 4	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg (Source: NLM_HSDB)
LD50 Dermal Rabbit	> 5000 mg/kg
Proprietary Ingredient 5	
ATE (Oral)	500.00 mg/kg body weight
ATE (Gases)	100.00 ppmV/4h
ATE (Vapors)	0.50 mg/l/4h
ATE (Dust/Mist)	0.05 mg/l/4h
Proprietary Ingredient 1	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Proprietary Ingredient 7	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rat	> 4000 mg/kg
LC50 Inhalation Rat	> 5235 mg/m ³ (Exposure time: 4 h Source: ECHA_API)
Proprietary Ingredient 14	
LD50 Oral Rat	3870 mg/kg (Source: NLM_HSDB)
Proprietary Ingredient 15	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rabbit	> 2500 mg/kg
LC50 Inhalation Rat	> 6.04 mg/l/4h

Skin Corrosion/Irritation: Causes severe skin burns.

Serious Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified.

Carcinogenicity: May cause cancer (Inhalation).

Proprietary Ingredient 1	
IARC group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Proprietary Ingredient 17	
IARC group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation).

Aspiration Hazard: Not classified.

UNICOAT FOAM and STUCCO PATCH

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/Injuries After Inhalation: Irritation of the respiratory tract and the other mucous membranes. Cough, dyspnea (breathing difficulty), wheezing; decreased pulmonary function, progressive respiratory symptoms (silicosis). The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels. Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis. Progressive massive fibrosis may occur in simple or accelerated silicosis, but is more common in the accelerated form. Progressive massive fibrosis results from severe scarring and leads to the destruction of normal lung structures.

Symptoms/Injuries After Skin Contact: Causes severe irritation which will progress to chemical burns. May cause an allergic skin reaction. Cement may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns. A skin exposure may be hazardous even if there is no pain or discomfort. Cement is capable of causing dermatitis by irritation and allergy. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Irritant dermatitis is caused by the physical properties of cement including alkalinity and abrasion. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in cement. The reaction can range from a mild rash to severe skin ulcers. Persons already sensitized may react to the first contact with cement. Others may develop allergic dermatitis after years of repeated contact with cement.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva. Airborne dust may cause immediate or delayed irritation or inflammation. Eye contact with large amounts of dry powder or with wet cement can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

Symptoms/Injuries After Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic Symptoms: Causes damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation). May cause cancer (Inhalation). This product contains crystalline silica. Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis; a seriously disabling and fatal lung disease, and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects. Inhalation may lead to a progressive massive fibrosis which may be accompanied by right heart enlargement, heart failure, pulmonary failure of the lung and susceptibility to pulmonary tuberculosis. Pulmonary function may be reduced and pre-existing lung diseases such as: emphysema or asthma may be aggravated by inhalation exposure to dusts. Smoking aggravates the effects of exposure.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Not classified.

Proprietary Ingredient 15	
LC50 Fish 1	50.6 mg/l
Proprietary Ingredient 17	
LC50 Fish 1	36.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC50 Fish 2	7.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

12.2. Persistence and Degradability

UNICOAT FOAM and STUCCO PATCH	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

UNICOAT FOAM and STUCCO PATCH	
Bioaccumulative Potential	Not established.
Proprietary Ingredient 15	
BCF Fish 1	(no bioaccumulation)

12.4. Mobility in Soil

No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment.

UNICOAT FOAM and STUCCO PATCH

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Not regulated for transport

14.2. In Accordance with IMDG

Not regulated for transport

14.3. In Accordance with IATA

Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

UNICOAT FOAM and STUCCO PATCH	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Carcinogenicity Health hazard - Respiratory or skin sensitization Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation
Proprietary Ingredient 2	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Proprietary Ingredient 4	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Proprietary Ingredient 5	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Proprietary Ingredient 3	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Proprietary Ingredient 1	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Proprietary Ingredient 6	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Proprietary Ingredient 10	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Proprietary Ingredient 8	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Proprietary Ingredient 11	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Proprietary Ingredient 7	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Proprietary Ingredient 14	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Proprietary Ingredient 15	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	

15.2. US State Regulations

Proprietary Ingredient 2	
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List	
Proprietary Ingredient 4	
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List	
Proprietary Ingredient 3	

UNICOAT FOAM and STUCCO PATCH

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Massachusetts - Right To Know List

Proprietary Ingredient 1

U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Massachusetts - Right To Know List

Proprietary Ingredient 9

U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Proprietary Ingredient 14

U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Massachusetts - Right To Know List


Proprietary Ingredient 15

U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Massachusetts - Right To Know List

Proprietary Ingredient 17

U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

California Proposition 65

 **WARNING:** This product can expose you to Chromium, ion (Cr6+), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Quartz (14808-60-7)	X			
Chromium, ion (Cr6+) (18540-29-9)	X	X		

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 06/11/2024
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Glossary of Data Source Abbreviations

ATSDR: Agency for Toxic Substances and Disease Registry (U.S. Department of Health and Human Services)
 AU_WES: Australia WES

FOOD_JOURN: Food Research Journal (1956)
 IARC: The International Agency for Research on Cancer
 IDLH: National Institute for Occupational Health and Safety Immediately

UNICOAT FOAM and STUCCO PATCH

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CHEMVIEW: ChemView (U.S. Environmental Protection Agency)

EC_RAR: European Commission Renewal Assessment Report

EC_SCOEL: European Commission Scientific Committee on Occupational Exposure Limits

ECETOC: European Centre for Ecotoxicology and Toxicology of Chemicals Reports

ECHA_API: European Chemicals Agency API

ECHA_RAC: ECHA Committee for Risk Assessment

EFSA: European Food Safety Authority

EPA: U.S. Environmental Protection Agency

EPA_AEGL: Acute Exposure Guideline Levels (U.S. Environmental Protection Agency)

EPA_FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act Reregistration Eligibility Decision (U.S. Environmental Protection Agency)

EPA_HPV: High Production Volume Chemicals (U.S. Environmental Protection Agency)

EPA_TRED: Risk Assessment for Tolerance Reassessment Eligibility Decision (U.S. Environmental Protection Agency)

EU_CLH: European Union Harmonised Classification and Labelling Proposal

EU_RAR: European Union Risk Assessment Report

Dangerous to Life or Health Value Profiles

IUCLID: International Uniform Chemical Information Database

JAPAN_GHS: Japan GHS Basis for Classification Data

JP_J-CHECK: Japan J-Check

KR_NIER: South Korea National Institute of Environmental Research Evaluations

NICNAS: Australia National Industrial Chemicals Notification and Assessment Scheme

NIOSH: National Institute for Occupational Health and Safety (U.S. Department of Health and Human Services)

NLM_CIP: National Library of Medicine ChemID plus database

NLM_HSDB: National Library of Medicine Hazardous Substance Data Bank

NLM_PUBMED: National Library of Medicine PubMed database

NTP: National Toxicology Program

NZ_CCID: New Zealand Chemical Classification and Information Database

OECD_EHSP: Environment, Health, and Safety Publication (Organisation for Economic Co-operation and Development)

OECD_SIDS: Screening Information Data Sets (Organisation for Economic Co-operation and Development)

WHO: World Health Organization

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)